

Type	BIOFUSION
------	-----------



* Flow rate and capacities may vary in accordance with the water quality

Model IRON CLEAR		1044	1248	1354	1465
Specification					
liters of media	litres	30	60	75	90
nominal flow*	m3/h	0,7	1	1,2	1,5
peak flow*	m3/h	1,4	1,8	2,2	2,4
fitings	"	1"	1"	1"	1"
iron removal	m3/ppm	15	15	15	15
hydrogen sulfite removal	m3/df	1	1	1	1
pH range	m3/dH	6	6	6	6
Components					
valve	type	Clack WS1 Clack Impression Sulfur Plus	Clack WS1 Clack Impression Sulfur Plus	Clack WS1 Clack Impression Sulfur Plus	Clack WS1 Clack Impression Sulfur Plus
tank	type	1044	1248	1354	1465
accessories		Internal check valve assy backwash air filter	Internal check valve assy backwash air filter	Internal check valve assy backwash air filter	Internal check valve assy backwash air filter
		transformer 12V	transformer 12V	transformer 12V	transformer 12V
drain size (DLFC)	"	3/4"	3/4"	3/4"	1"
BLFC	gpm	0,5	0,5	0,5	0,5
DLFC	gpm	4,2	5,3	6,5	9
injector		red (1D)	white (1E)	blue (1F)	yellow (1G)
Regeneration					
backwash air	minutes	4	4	4	4
	litres	60	88	102	108
backwash	minutes	10	10	10	10
	litres	190	304	380	420
regenerat draw	minutes	60	60	60	60
	litres	95	152	190	210